

<b>Dimensions--Internal</b>	<b>20' Standard</b>	<b>40' Standard</b>	<b>40' High Cube</b>
<b>Length:</b>	19' 4.0"	39' 6.0"	39' 6.0"
<b>Width:</b>	7' 9.0"	7' 9.0"	7' 9.0"
<b>Height:</b>	7' 10.0"	7' 10.0"	8' 10.0"
<b>Door Opening Width:</b>	7' 8.0"	7' 8.0"	7' 8.0"
<b>Door Opening Height:</b>	7' 6.0"	7' 6.0"	8' 5.0"
<b>Cubic Capacity:</b>	1,169 ft <sup>3</sup>	2,384 ft <sup>3</sup>	2,698 ft <sup>3</sup>

#### **Weight & Payload**

<b>Tare Weight</b> ( <i>Design Estimate</i> ):	4,915 lbs.	8,070 lbs.	8,465 lbs.
<b>Maximum Gross Weight:</b>	67,200 lbs.	67,200 lbs.	67,200 lbs.
<b>Maximum Payload:</b>	62,285 lbs.	59,130 lbs.	58,735 lbs.

#### **Strength Tests**

<b>Floor:</b>	16,000 lbs.*	16,000 lbs.*	16,000 lbs.*
---------------	--------------	--------------	--------------

#### **Stacking**

<b>Stacking Height:</b>	8 High	8 High	8 High
<b>Stacking Test Load per Post:</b>	211,226 lbs.	211,226 lbs.	211,226 lbs.

#### **Cargo Lashing System**

<b>Lashing Rings:</b>	8 per side	16 per side	16 per side
<b>Lashing Bars:</b>	2 per corner	2 per corner	2 per corner

#### **Ventilation**

<b>Ventilators:</b>	2 total	4 total	4 total
---------------------	---------	---------	---------

\* Five passes with ISO compliant test vehicle